



SPACEREFLEX®
FÁBRICA DE ISOLAMENTO TERMO-ACÚSTICO
FACTORY OF THERMO-ACOUSTIC INSULATION

SOMOS FABRICANTES
WE ARE MANUFACTURERS
NOUS SOMMES FABRICANTS

TECHNICAL SPECIFICATIONS





Technical Data

- | | |
|-------------------------------|-----------------|
| • Weight | 46 (Gr. /M2) |
| • Thickness (NP EN822/ EN823) | 2 mm (± 2%) |
| • Width (NP EN822/ EN823) | 1,20 m (± 2,5%) |
| • Length (NP EN822/ EN823) | 15m (± 2,5%) |

Applications

- Construction / Rehabilitation of buildings;
- Modular Construction – Wood, LSF (Light Steel Framing);
- Packaging (Thermal Boxes / Containers).



Precautions:

- Once the product may contain some residual flammable gas, it must be stored in a ventilated area, and avoid placing it within the reach of the flame.

SECTOR:

- ✓ Residential
- ✓ Commercial
- ✓ Industry

Increase energy savings

Use SPACE REFLEX insulation!

Acoustic Insulation

Ref.	Length x Width	Area	Ø
FLOOR2	15m x 1,20m	18m2	± 20 cm

COMPOSITION

Formed by a polyethylene foam layer, laminated on the outer faces with aluminized film.

Benefits:

- Quick and easy to install;
- Easy to handle;
- Lightweight and flexible;
- Does not require special tools, equipment or any kind of special clothing;
- Do not harmful to human health;
- Reduced thickness.
- Does not contain CFC ;
- Excellent water resistance ;
- Good resistance to sunlight and the solvents except chlorinated aliphatic hydrocarbons;
- Good thermal insulation (Radiation and conduction).

FÁBRICA / FACTORY
AV. DRA. ASSUNÇÃO VASCONCELOS CHAVES, LOTE C1
DUME - APARTADO 2603
4701-907 BRAGA - PORTUGAL

T +351 253 331 065
F +351 253 331 066
E INFO@SPACEREFLEX.COM
W WWW.SPACEREFLEX.COM

